

UTLX 88162

CAPACITY 60000 LBS.

U.T.C. CO. WT. 32200 12 11

U.T.L.X. 1104S

WT 33600 NEW 1 12

0123456789

0123456789

UTLX

UTLX

1104S

88162

0123456789

SAFETY VALVES
TESTED 9-16-63
PRESSURE 25 LBS. PER SQ. IN.
AT ALAMOSA COLO.
BY D & R G W R R.
TANK
TESTED 9-16-63
PRESSURE 60 LBS. PER SQ. IN.
AT ALAMOSA COLO.
BY D & R G W R R.
HEATER 200 LBS.

SAFETY VALVES
TESTED 4-1-40
PRESSURE 25 LBS. PER SQ. IN.
AT ALAMOSA COLO.
BY D & R G W R R.
TANK
TESTED 4-1-40
PRESSURE 60 LBS. PER SQ. IN.
AT ALAMOSA COLO.
BY D & R G W R R.

UNION TANK CAR CO.

VV

6 X 7 COUPLER 9 1/2 BUTT
A R A NO.-2 BRAKE BEAM
CARDWELL GEAR G-14
HEATER PIPES C II
K-1 TRIPLE



RETAINER MUST NOT
BE USED IN THE 20 LBS.
POSITION ON EMPTY CAR

VV

5 X 7 COUPLER 6 1/2 BUTT
METAL BRAKE BEAM
CARDWELL GEAR G-14
TYPE-D-HEATER



RETAINER MUST NOT
BE USED IN THE 20 LBS.
POSITION ON EMPTY CAR

VV

5 X 7 COUPLER 9 1/2 BUTT
A R A No.2 BRAKE BEAM
CARDWELL GEAR G-14
TYPE-C-HEATER
K-1 TRIPLE

V

5 X 7 COUPLER 9 1/2 BUTT
A R A No.2 BRAKE BEAM
CARDWELL GEAR G-14
TYPE-R-HEATER
K-1 TRIPLE

0123456789